

Permeable Pavement Maintenance Requirements

Once a year, the Simple Infiltration Test shall be performed and any deficiencies in surface permeability shall be addressed.

At all times, the permeable pavement shall be kept free of:

- Debris and particulate matter through frequent blowing that removes such debris, particularly during the fall and spring.
- Piles of soil, sand, mulch, building materials or other materials that could deposit particulates on the pavement.
- Piles of snow and ice.
- Chemicals of all kinds, including deicers.

After the permeable pavement is constructed, it shall be inspected **semi-annually and within 24 hours after every storm event greater than 1.0 inches (or 1.5 inches if in a Coastal County)**. Records of operation and maintenance shall be kept in a known set location and shall be available upon request.

Inspection activities shall be performed as follows. Any problems that are found shall be repaired immediately.

SCM element:	Potential problem:	How to remediate the problem:
The perimeter of the permeable pavement	Areas of bare soil and/or erosive gullies have formed.	Regrade the soil if necessary to remove the gully, plant ground cover and water until it is established. Provide lime and a one-time fertilizer application.
	A vegetated area drains toward the pavement.	Regrade the area so that it drains away from the pavement, then plant ground cover and water until established.
The surface of the permeable pavement	Trash/debris is present.	Remove the trash/debris.
	Weeds are present.	Do not pull the weeds (may pull out media as well). Spray them with a systemic herbicide such as glyphosate and then return within the week to remove them by hand. (Another option is to pour boiling water on them or steam them.)
	Sediment has accumulated on the permeable pavement surface.	Remove the sediment with a mechanical sweeper, regenerative air cleaner or vacuum truck as appropriate.
	The permeable pavement surface is rutting, cracking, slumping or otherwise damaged.	Consult an appropriate professional.
Observation well	Water is present more than three days after a storm event.	Clean out any clogged underdrain pipes. Consult an appropriate professional for clogged soil subgrade.
Educational sign	The sign is missing or damaged.	Replace the sign.
The receiving water	Erosion or other signs of damage have occurred at the outlet.	Repair the damage and improve the flow dissipation structure.
	Discharges from the permeable pavement are causing erosion or sedimentation in the receiving water.	Contact Environmental Compliance Branch.